

Oracle

1Z0-932

Oracle Cloud Infrastructure 2018 Architect Associate



Question: 1

Which two parameters are required in a back end set's HTTP health check? (Choose two.)

- A. response body
- B. URL path
- C. timeout
- D. port
- E. status code

Answer: AE

Reference:

<https://docs.cloud.oracle.com/iaas/Content/Balance/Tasks/editinghealthcheck.htm>

Question: 2

Which two are true for achieving High Availability on Oracle Cloud Infrastructure? (Choose two.)

- A. Store your database across multiple regions so that half of the data resides in one region and the other half resides in another region.
- B. Attach your block volume from Availability Domain 1 to a compute instance in Availability Domain 2 (and vice versa) so that they are highly available.
- C. Configure your database to have Data Guard in another Availability Domain in Sync mode within a region.
- D. Store your database files on Object Storage so that they are available in all Availability Domains in all regions.
- E. Distribute your application servers across all Availability Domains within a region.

Answer: BE

Question: 3

Which two configuration formats does Terraform support? (Choose two.)

- A. YAML
- B. JSON
- C. HCL
- D. XML

Answer: BC

Reference:

<https://docs.cloud.oracle.com/iaas/Content/API/SDKDocs/terraformconfig.htm>

Question: 4

At the end of a terraform apply operation, what is the default output?

- A. nothing by default
- B. statistics about what was added, changed, and destroyed
- C. the entire state file
- D. statistics about what was added, changed, and destroyed, and the values of outputs

Answer: D

Reference:

<https://www.terraform.io/intro/getting-started/outputs.html>

Question: 5

You have created a public subnet in a VCN, and your public subnet has a Route Table, a Security List, and an Internet Gateway. However, none of the compute instances can connect to the Internet. Which two are possible reasons for the connectivity issue? (Choose two.)

- A. There is no Dynamic Routing Gateway (DRG) associated with the VCN.
- B. The Route Table has no default route for routing traffic to the Internet Gateway.
- C. There is no stateful ingress rule in the Security List associated with the public subnet.
- D. There is no stateful egress rule in the Security List associated with the public subnet.

Answer: BC

Question: 6

You want an instance in your compartment to make API calls to other services within Oracle Cloud Infrastructure without storing credentials in a configuration file. What do you need to do?

- A. No action is required. By default, all VM instances are created with an Instance Principal.
- B. Instances cannot access services outside their compartment.
- C. VM instances are treated as users. Create a user and assign the user to that VM instance.
- D. Create appropriate matching rules in the Dynamic Group to create an Instance Principal.

Answer: A

Reference:

<https://medium.com/@tigerbabu/oracle-cloud-infrastructure-associate-architect-notes-4495b25b24a4>

Question: 7

Which three must be configured for a load balancer to accept incoming traffic? (Choose two.)

- A. a listener
- B. a back-end server
- C. a back end set
- D. a security list that is open on a listener port
- E. a certificate

Answer: ADE

Reference:

<https://docs.cloud.oracle.com/iaas/Content/Balance/Tasks/managinglisteners.htm>

Question: 8

Which two statements are true about Oracle Cloud Infrastructure Compute Service? (Choose two.)

- A. You can launch a virtual or bare metal instance by using the same LaunchInstance API.
- B. You cannot launch a bare metal server in Oracle Cloud Infrastructure Compute Service.
- C. You can attach a block volume in an Availability Domain other than your compute instance.
- D. You can share custom images across tenancies and regions.

Answer: AD

Reference:

<https://docs.cloud.oracle.com/iaas/Content/Compute/Tasks/imageimportexport.htm>

Question: 9

Which five are the required parameters to launch an instance in Oracle Cloud Infrastructure? (Choose five)

- A. subnet
- B. Availability Domain
- C. Virtual Cloud Network

- D. host name
- E. instance shape
- F. image operating system
- G. private IP address

Answer: ABCEF

Reference:

<https://docs.cloud.oracle.com/iaas/Content/Compute/Concepts/computeoverview.htm>

Question: 10

Which DNS resource record type is used to point a host name to an IPv4 address?

- A. ALIAS
- B. A
- C. CNAME
- D. AAAA

Answer: B

Reference:

<https://docs.cloud.oracle.com/iaas/Content/DNS/Reference/supporteddnsresource.htm>

Question: 11

Which three can you achieve by using Terraform? (Choose three.)

- A. Create resources in the right order without regard to the order in the terraform plan file.
- B. Automatically re-provision the resources that are tainted or whose configuration has changed.
- C. Automatically translate a deployed infrastructure and create a plan.
- D. Automatically destroy all the resources that are in tenancy.
- E. Continuously maintain the configuration files in an instance.

Answer: ABD

Question: 12

Your application front end consists of several Oracle Cloud Infrastructure compute instances behind a load balancer instance. You have configured the load balancer to perform health checks on these instances.

If an instance fails to pass health checks, what will happen?

- A. The instance is replaced automatically by the load balancer.
- B. The instance is terminated automatically by the load balancer.
- C. The instance is taken out of the back end set by the load balancer.
- D. The load balancer stops sending traffic to that instance.

Answer: D

Question: 13

Which statement is true about cloning a volume?

- A. You need to detach a volume before cloning from it.
- B. A cloned volume is the same as a snapshot that has a dependency on the source volume.
- C. You cannot change the block volume size when cloning a volume.
- D. You can create a clone for a volume across regions.

Answer: C

Reference:

<https://docs.cloud.oracle.com/iaas/Content/Block/Tasks/cloningavolume.htm>

Question: 14

Which scaling option does Database Cloud Service (DBCS) on Bare Metal Shape offer?

- A. network bandwidth
- B. CPU
- C. storage
- D. memory

Answer: C

Reference:

<https://cloud.oracle.com/iaas/database/faq>

Question: 15

Which statement is true about Oracle Cloud Identifiers (OCID)?

- A. mytenancy.oc.ocid is a valid OCID.
- B. If you delete a user, and then create a new user with the same name, the user will be considered a

different user because of different OCIDs.

C. Users can customize OCIDs for all the resources in their compartments.

D. If you delete a user, and then create a new user with the same name, the new user will be assigned the exact same OCIDs as the system remembers.

Answer: B

Reference:

<https://docs.cloud.oracle.com/iaas/Content/Identity/Tasks/managingusers.htm> (see note)

For More Information – **Visit link below:**
<https://www.testsexpert.com/>

Features:

■ Money Back Guarantee.....



■ 100% Course Coverage.....



■ 90 Days Free Updates.....



■ Instant Email Delivery after Order.....

